

**Intermec**

## Product Profile



- Superior throughput eliminates wait time at the printer
- Heavy-duty metal construction withstands harsh / rugged environments
- Compact size for demanding applications where space is limited
- Supports stand-alone printer applications
- Easily adapts to changing host environments and applications
- Can emulate and replace competitive and older Intermec printers
- CompactFlash memory for quick and easy firmware, font, and memory upgrades
- Utilize up to five interface ports simultaneously, including internal EasyLAN™ Ethernet or EasyLAN Wireless
- Magnetic QuickMount™ printhead for easy printhead installation
- User selectable printer language

### **E a s y C o d e r ® P F 4 c i P R I N T E R**

The EasyCoder PF4ci is an industrial printer designed to excel in demanding applications and environments where space is limited. Utilizing the latest technology, it features a strong and proven mechanical platform, and powerful newly developed electronics.

The EasyCoder PF4ci can act as a "smart client" executing user-defined programs. This means that your printer can eliminate the PC, operate additional hardware (e.g. scanners, other printers, conveyors), access information from the network, and retains the ability to change as needed with the application for additional functionality. When using the EasyLAN Wireless option, any attached peripheral devices also become part of the wireless infrastructure.

Printer command languages do not restrict the EasyCoder PF4ci. The PF series printers can emulate and replace competitive and older Intermec printers without requiring any changes to the host programming or label formats.

The EasyCoder PF series features optional integrated wired or wireless EasyLAN networking. The wireless interface uses an integrated standard 802.11b/g radio providing 128-bit WEP encryption of the information relayed through the network.

The magnetic QuickMount printhead eliminates hassles and downtime. The printhead is replaced quickly and easily with the magnet and u-brackets ensuring proper alignment. The double-clutching ribbon mechanism means that you are not restricted to ribbon types based on how they are wound. The handy, inexpensive and PC-compatible CompactFlash™ memory technology provides quick and easy memory expansion for extra storage of formats, graphics, fonts, and an easy way to update printer firmware.

The EasyCoder PF4ci bar code printer is exceptionally fast in throughput and printing, reliable, and delivers very high print quality.

**Intermec**

**Application**

Direct Thermal and Thermal Transfer label, ticket and tag printer.

**Physical Characteristics**

**LxHxW:** 405 x 178 x 244 mm

(15.9 x 7.0 x 9.6 in)

**Weight:** 8 kg (17.7 lbs.)

**Print Specifications**

**Max. Width:** 104 mm (4.09 in) at 203 dpi; 105.7 mm (4.16 in) at 300 dpi.

**Max. Length w/ std memory:** 2520 mm (99.2 in) at 203 dpi; 1092 mm (43.0 in) at 300 dpi.

**Max length w/ 16MB SDRAM:** 4095 mm (161.2 in) at 203 dpi; 2730 mm (107.5 in) at 300 dpi.

**Print Speed**

Up to 76 labels per minute. 101x152mm (4x6 in) GM1724 label. To learn more, please visit [www.intermec.com/printspeed](http://www.intermec.com/printspeed).

**Print Direction**

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

**Print Resolution**

8 dots/mm (203 dpi), 11.8 dots/mm (300 dpi)\*

**Label/Ticket/Tag**

**Max. Width:** 114.3 mm (4.5 in)

**Min. Width:** 25.4 mm (1 in)

**Thickness:** 2.5 to 8.7 mil

**Style:** Roll-fed, die-cut, continuous or fanfold labels, tags or tickets

**Label Roll max diameter:** 150 mm (6.0 in)

**Label Roll Core:** 38-76 mm (1.5-3 in)

**Media Type:** Thermally sensitive media

**Ribbon Roll**

**Ribbon roll max diameter:** 65 mm (2.56 in) or approx. 300 m (980 ft) of ribbon

**Ribbon Roll Core:** 25 mm (1 in)

**Ribbon Type:** Wax, wax/resin, resin

**Interfaces****Standard:**

- RS-232, up to 115.2 kB/s
- USB 1.1

- Wand interface for EasySet™ System

**Optional**

- EasyLAN Wireless internal Ethernet
- EasyLAN 10/100BaseT internal Ethernet

**Optional interface card adapters:**

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop

**Network Interface Options:**

**EasyLAN intergrated Ethernet:** RJ-45 connector for 10BaseT or 100baseTX

**EasyLAN Wireless**

- Fully integrated IEEE 802.11b/g
- WEP 128 bit
- Multiple industrial antenna options for maximized coverage

**Supported Protocols:** TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP.

SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

**Software****Available printer command languages:**

- IPL
- Fingerprint/Direct Protocol

**Applications/Drivers (comes on Printer Companion CD) including:**

- InterDriver™ Windows printer driver
  - Intermec LabelShop® START label design and print package
  - Intermec Printer Network Manager for administration of networked printers
  - PrintSet for printer configuration
- Optional software for application development:**
- Fingerprint ApplicationBuilder™
  - Intermec Printer Application Server™
  - ERLabel™ for SAP™ R/3®.

**Bar Code Symbolologies**

**Fingerprint/DP 1-dimensional:** Codabar, Code 11, Code 39, Code 39 full ASCII, Code 39 w. checksum, Code 93, Code 128, Code 128 Subset A-C, DUN-14/16, EAN-8, EAN-13, EAN-128, EAN-128 Subset A-C, Five-Character Supplemental Code, Industrial 2 of 5, Industrial 2 of 5 w. checksum, Interleaved 2 of 5, Intereaved 2 of 5 w. checksum, Interleaved 2 of 5 A, Matrix 2 of 5, Postnet, Straight 2 of 5, Two-Character Supplemental Code, UCC-128 Serial Shipping Container Code, UPC-5 digits Add-On Code, UPC-A, UPC-D1 to D5, UPC-E, UPC Shipping Container Code

**Fingerprint/DP 2-dimensional:** Code 16K, Code 49, Data Matrix, MaxiCode, MSI(modified Plessey), PDF 417, Plessey, QR Code, MicroPDF417

**IPL 1-dimensional:** Codabar, Code 11, Code 39, Code 93, Interleaved 2 of 5, Code 2 of 5, Code 128, UCC-128 Serial Shipping Container Code, UPC/EAN Codes(EAN 8, EAN 13, UPC Version A, UPC Version E), HIBC Code 39, Postnet, HIBC Code 128

**IPL 2-dimensional:** Code 16K, Code 49, PDF417, Maxicode, JIS-ITF, Data Matrix, QR Code, MicroPDF417

**Standards Supported**

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; HIBCC; ISBT 128; GM1724; UPS shipping label; Global Transport label

**Character Sets**

**Fingerprint/DP:** 15 TrueDoc™ (scalable) fonts including 12 UNICODE (1 WGL4), 1 symbol, 1 OCR-A, 1 OCR-B. Font cache for maximum performance. ATF font support. Non-Latin fonts are available as options.

**IPL:** 13 TrueDoc (scalable) fonts + 20 bitmap fonts.

**Graphics**

Supports PCX file format.

**Memory**

**Standard:** 4MB Flash memory  
8MB SDRAM

1 Compact Flash slot  
**Optional:** Flash memory: Up to 16MB totally. (8+8MB)  
1GB CompactFlash memory  
SDRAM: Up to 16MB totally

**Protocol**

**Fingerprint/Direct Protocol:** XON/XOFF, ENQ/ACK, DTR, RTS/CTS

**IPL:** XON/XOFF, Intermec Std. Protocol

**Display**

Back-lit LCD for 2x16 characters and 3 LED indicator lamps

**Keypad Control Panel**

- Full keypad control panel (Fingerprint/DP)
- Simplified keypad control panel (IPL)

**Power Supply**

115/230VAC auto-switch w/PFC

**Voltage Range:** 100-240 VAC ±10%.

**Frequency Range:** 45-65 Hz

**Operating Environment**

**Temperature:** +5° to +40°C (+40° to +104°F)

**Humidity:** 20-80% RH non-condensing

**Noise:** 50 dB (printing), no noise standby

**Regulatory Approvals**

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

**Options**

Integral Self-Strip Unit with Liner Takeup, Label Taken Sensor (LTS), CompactFlash (CF) Memory, Flash and SDRAM SIMM, Various International Double Byte Fonts\*, EasySet Bar Code Wand\*, External RS-232C Alphanumeric Keyboard\*, Parallel Interface Board, Additional Serial Interface Board\*, Industrial Interface Board\*, Real Time Clock\*, Media Supply Hub, Cutter

\*Not applicable when using IPL firmware

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/  
Middle East & Africa**

**Headquarters**  
Sovereign House  
Vastern Road  
Reading RG1 8BT  
United Kingdom  
tel: 44.118.987.9400  
fax: 44.118.987.9401

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

Intermec International Inc  
14 Floor, IBM-Pacific Century Plaza  
2A Workers Stadium  
Chaoyang District, Beijing 100027  
P.R. China  
Tel: +86 (010).6539 1012  
Fax: +86 (010).6539 1025

**Australia**

Level 7, 200 Pacific Highway  
Crowns Nest, NSW 2065  
Australia  
tel: 61.2.9492.4400  
fax: 61.2.9954.6300

**South America & Mexico**

Intermec South America Ltda.  
Rua Arandu 1544-15 andar  
Edificio Itavera  
Brooklin Novo 04562-031  
Sao Paulo, SP  
Brazil  
tel: 55.11.5501.2070

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.211.1919  
fax: 525.55.211.8121

**Worldwide**

**Fax Document  
Retrieval Service**  
800.755.5505  
(North America Only)  
tel: 650.556.8447

**Internet**

[www.intermec.com](http://www.intermec.com)

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2003 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.  
611466-01A 12/03

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

**Intermec®**  
e x p e c t **MORE™**