

# Bar Code Scanners



## 8700 Bluetooth® Bar Code Imager

- Linear imaging of 1D or 2D bar codes, from 1 - 80 inches.
- Industry leading Bluetooth range.
- Configurable aiming dot feature.
- Unsurpassed reading of poor quality bar codes.
- Industrial ergonomics including: IP65; 6.6-ft drops to concrete; -20° C operating temp.
- Able to pair with LXE computer via a simple scan of the computer's bar code.
- Full line of accessories available including: 4-slot battery charger, belt holster, take-up reel, and more.

## 8600 Series Bar Code Scanners

- 2D imager ring with 21" scan distance.
  - Enhanced white LED flash illumination.
- SR laser ring with 45" scan distance.
- Either available with long cables to attach to hip flip or voice case.



## 8500 Series Bar Code Scanners 8800 Bluetooth® Bar Code Scanner

- Extended range scanning from 4 inches to 45 feet.
- Easily reads damaged or poorly printed bar codes (fuzzy logic technology).
- Industrial ergonomics including: IP65, 6.5-ft (2M) drop test, -22° F operating temp.

## 8300 Series PowerScan™ Industrial Bar Code Scanners

- QuadraLogic™ II decoding software for superior scanning performance.
- Available in Standard, Long & Advanced Long Range.
- Advanced Long Range can scan bar codes as far away as 36 feet.



**LXE is YOUR RUGGED SCANNER SOURCE.**

*Of course, all LXE Bar Code Scanners and Imagers are supported by LXE's award-winning support team, winners of the Mobile Star Award™ for best customer service six years in a row.*





125 Technology Parkway Norcross, GA 30092 1-800-664-4593 [www.lxe.com](http://www.lxe.com)

# Bar Code Scanners

## Technical Specifications



	Scan Rate	Depth of Field	IP Rating	Temp Range	Symbologies Supported
 <p><b>8700 Bluetooth® Imager</b></p>	8700 SRI 500/ sec.	8700 SRI Min. 1" Max. 80"	8700 SRI IP65	8700 SRI -4° to 122° F	8700 SRI UPC/EAN/JAN, P2/P5 add-ons, Code 39, Micro PDF, Code 128 ISBT, Code 11, EAN 128, MSI/Plessey, Standard 2 of 5, Code 128, PDF-417, IATA, Italian Pharmacode 39, Code 93, Codabar, Code 128 add-ons, Interleaved 2 of 5, RSS-14/limited/expanded (linear & stacked), Composites CC-A and CC-B (only RS composites)
 <p><b>8600 Series</b></p>	8600 SRS Imager Series  8600 SRS Laser Series 36/ sec.	8600 SRS Imager Min. 3.5" Max. 21"  8600 SRS Laser Scanner Min. 1" Max. 45"	8600 SRS Imager IP54 8600 SRS Laser Scanner IP54	8600 SRS Imager -4° to 122° F 8600 SRS Laser -4° to 122° F	8600 SRS Imager & Laser Scanner -1D Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, Interleaved 2 of 5, MSI Plessey, RSS, UPC/EAN: UPC-A, UPC-E, UPC-E1, EAN-8, EAN-13  8600 SRS Imager - 2D PDF417, MicroPDF, Code 128 Emul, Data Matrix, Maxicode, QR Code, Postal Codes
 <p><b>8500 Series</b> <b>8800 Bluetooth® Series</b></p>	8500 FZY 8810 FZ 8500 ER 8820 ER  36/ sec.	8500 FZY 8810 FZ Min. 4.0" Max. 84" 8500 ER 8820 ER Min. 4" Max. 45"	8500 FZY 8810 FZ IP65 8500 ER 8820 ER IP65	8500 FZY 8810 FZ -22° to 122° F 8500 ER 8820 ER -22° to 122° F	8500 FZY, 8810 FZ, 8500 ER and 8820 ER UPC.EAN, UPC.EAN with Supplementals, UCC.EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants, and others
 <p><b>8300 Series</b></p>	8300 SR 37/ sec. 8300 LR & ALR 35/ sec.	8300 SR Min. .2" Max. 60" 8300 LR Min. 5.0" Max. 22" 8300 ALR Min. 28" Max. 36"	8300 SR IP54 8300 LR & ALR IP54	8300 SR -22° to 122° F 8300 LR & ALR -22° to 122° F	8300 SR, LR & ALR UPC A, E / EAN 8,13 / JAN 8, 13 (P2 / P5, Code 128 EAN add-ons), Code 128, MSI / Plessey, Code 39, Interleaved 2 of 5, Code 39 Full ASCII, Standard 2 of 5, Code 93, Codabar, Pharmacode 39, BC412, and others



\*RoHS compliant versions available for all LXE scanners



ORACLE PARTNER

