

# MS146

# Barcode Slot Reader



#### MS 146 Barcode Slot Reader

The MS146 bar code slot reader applies for time control, security access, or attendance control applications with pre-printed forms and scanning cards or badges. It is also an ideal economic device either for desk-top or for multidirection for side-mounted applications on the wall, which interface with all popular devices. The MS146 slot reader has a wide slot and features perfect read rates on high density labels with its resolution of 0.15mm. It's sealed optical system with IP54 rugged housing allows MS146 read the label in the harshest industrial environment without degrading its performance.

# **Features**

- · Sealed optical system with IP54 rugged housing · Wide bar code slot with flexible reading angle and higher resolution
- - · Multi-direction for flexibility of installation · User configurable via PC programming
  - · Compatibility with all popular computer and devices
  - · Provide desktop or side-mounted application on the wall
- · Suitable for different cards of different dimension and printing qualities
  - Available with TTL, keyboard wedge RS232 and USB interfaces
    - · Advanced Data Editing
    - 50 mm to 700 mm/sec Scan Rate
      - 6 mil minimum resolution

# **Optical**

Sensor

Light Source Infrared: 930 nm LED Visible light: 660 nm LED

Photo diode

Depth of field 2 mm

Resolution 6 mils (0.15mm) min Print Contrast 0.6 minimum Scan Speed 50 ~ 700mm/Sec M.T.B.F 25000 Hours

### **Functionality**

Symbologies Code 39 standard and full ASCII, EAN-13, UPC-A, EAN-8,

UPC-E, standard 2 of 5, Code 128, Code 93, MSI, Code 11, Code 32, Delta Code, Label Code, Plessey

Code, Codabar

Interface USB, Keyboard wedge, RS232, TTL (undecoded)

# **Mechanical and Electrical**

Dimensions 128 mm (L) x 53 mm (W) x 33 mm (H)

Weight

Power consumption 35 mA for TTL 5V DC 5%

70mA for Decoded version

Beep sound volume

# **Environmental**

0 C° to 50 C° Operating Temperature Storage Temperature -20 C° to 60 C°

Humidity 0% to 95% RH non-condensing Mechanical Shock 5 ft. (1.5 m) drop on concrete











# **Unitech America**

Los Angeles, Houston, Guadalajara http://www.ute.com e-mail: inquiry@ute.com http://latin.unitech-adc.com e-mail: info@latin.ute.com

# **Unitech Asia Pacific & Middle East**

http://www.unitech-utp.com.tw e-mail: aidcsales@tw.ute.com

## **Unitech Japan**

http://www.unitech-japan.co.jp e-mail: sales@unitech-japan.co.jp

#### Unitech Europe

Tilburg / Netherlands http://www.unitech-europe.com e-mail: sales@unitech-europe.com

### **Unitech Greater China**

Beijeng, Shanghai, Guang Zhou, Xiamen http://www.ute.com.cn e-mail: unitech@cn.ute.com Taipei http://adc-utt.unitech.com.tw barcode@tw.ute.com

#### **Head Office**

http://www.unitech-adc.com e-mail: marketing@tw.ute.com