

unitech

MT650

Video T&A Terminal



The MT650 is upgraded as a multifunctional terminal performing capabilities of Time Management, Access control, Intercom, and Surveillance with a large, 480 by 640 pixels, VGA color touch screen and the familiar interface of Windows CE operating system. It works as a mini-Kiosk station on top of a variety of applications. Users increase productivity right from the start, and application development is easier than ever. It is designed to meet the requirements of Time & Attendance, Loyalty Programs, Intercom and Work-In-Process applications; it can communicate with a central host security and T&A system via standard Ethernet or WLAN networks. Moreover MT650 seizes completely control over area security with its built-in CMOS digital camera, microphone, and audio speaker. Multiple I/O ports and interfaces make it the ideal solution for complex. The MT650 features built-in variety readers such as proximity and 1:N finger print, this permits the user to choose the technology that results in a cost-efficient system. Powered by Windows CE.NET 6.0, the MT650 package includes programming tools and support software for developing custom security and T&A applications.

Main Features

- Powered by WindowsCE.NET 6.0
- Large 480 by 640 pixel color VGA display with touch screen
- Built-in bar code, proximity, Mifare, 1:1 fingerprint reader, HID or 1:N fingerprint reader
- Built-in 2.0 M pixels CMOS camera
- Speaker output, microphone input
- Two relay output controls (small size)
- Two TTL digital inputs (Optical input)
- Built-in UPS for 1 hour operation and keeps 6 days of RTC
- Optional wireless communication support high speed wireless LAN 802.11b/g
- VoIP
- SDIO
- Ethernet with optional POE, (power over Ethernet)
- RS232/RS485 port



▶ Performance Characteristics

OS	WindowsCE.NET 6.0
CPU	Samsung 6410
DDR	256MB
FlashROM	NAND 256MB

▶ Readers

EM	125 kHz
MiFare	13.56 MHz
HID	125 kHz
Barcode reader	

▶ Fingerprint Input

EER < 0.1%
1:1 verification time < 1 sec
1:N Identification time < 1 sec
Template capacity : 1900

▶ Camera

2.0M pixel CMOS

▶ Keyboard

6 hard keys	CLK/IN (F1) CLK/OUT (F2)
	BRK/IN (F3) BRK/OUT (F4)
	Enter (Yes) ESC (No)

▶ Wireless Communication

Optional 802.11 b/g

▶ Outline & Appearance

Dimension	223L x 168W x 51H
Weight	1310g

▶ Display

5.7" TFT - LCD VGA (480 X 640) color

▶ I/O

Digital inputs	2
Output relays	2
Audio speaker	0.8W
Ethernet connection	One RJ45 with optional PoE (Compliant IEEE 802.3af)

▶ Power Management

Power Input	DC 12V/2A
UPS	One rechargeable Lithium-ion battery pack 7.4V, 1200 mAH, to operate for 1 hour after DC-Off

One Micro-backup battery for keeping RTC data 6 days

▶ Expansion

SDIO for SDHC memory storage, up to 16 GB
USB Host 1.1

▶ Physical and Environmental

Humidity 5% to 95% RH non-condensing
Operation temperature : -10 °C to 50 °C
Storage temperature : -4 °F to 158 °F (-20 °C to 70 °C)

▶ Software Programming Tools

Embedded Visual C++
Visual Studio C# / VB.NET
WinCE platform SDK
Video & Voice SDK



TASHI

Taipei
<http://www.ute.com> e-mail: TASHI@hq.ute.com

Unitech America

Los Angeles, Houston
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

Unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

Unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com

Head Office

Taipei
<http://www.ute.com> e-mail: info@hq.ute.com