



The Most Reliable Portable Printers.®

microFlash® 2t Serial & Wireless Portable Thermal Printer

The microFlash 2t offers the most reliable performance available, printing outstanding quality 2" direct thermal receipts, proofs of delivery, labels and invoices. Whether in serial or wireless mode, the small and lightweight 2t is the printer of choice around the globe for route accounting, direct store delivery (DSD), field service, logistics, home delivery and pre-sales systems. Its reliable print mechanism offers outstanding print clarity, allowing the printing of graphics, bar codes and logos. The 2t is recognized worldwide for providing the most reliable 2" printing, shift after shift, month after month, year after year.

Rugged and Reliable. With uncompromising standards, the 2t is engineered throughout to withstand even the most punishing portable applications. It is the only portable 2" printer that provides the durability required in the demanding field mobile environment. Designed to take multiple 6' drops to concrete, the unbreakable double-walled polyethylene case protects your investment; taking all the bumps and knocks inherent in the mobile workplace. The 2t's rock solid print mechanism is proven to provide years of service where other printers fail. The full one year warranty, even on the printhead, offers peace of mind with our promise to stand behind every product we sell.

Wireless Printing. When you need wireless, count on O'Neil to offer the most reliable solution. Both our 802.11b wireless local area network (WLAN) and our Bluetooth® wireless personal area network (WPAN) modules eliminate the need for mobile workers to return to their vehicle to print receipts or tickets. O'Neil is the first portable printer manufacturer to incorporate the Bluetooth protocol in Flash memory, eliminating the need for costly software and hardware upgrades whenever the wireless specification changes.

Power to Spare. The 2t uses one 6V NiMH, 2150 mAh (DR10®) battery. Its automatic sleep mode saves power and the fast 3-hour recharging time, along with an optional vehicle charger, provides the ideal solution for long and intense printing applications.

Flash Memory. As your business changes, so might your printer needs. We pioneered the use of Flash memory many years ago allowing you to change fonts and functions simply by connecting the printer to a computer. No need to return the printer for an upgrade.

We Speak Your Language – Any Language. O'Neil has eliminated the font and character limitations found in other printers. In cooperation with Bitstream® fonts, any international character set can be added to the 2t with a one-time minimal setup fee.



“Companies, some of which have discovered the hard way that standard printers are not durable in the field, are increasingly seeking ruggedized options. ‘We’ve been replacing a lot of mobile printers that weren’t cut out for the demands of the mobile workforce.’”

Business Solutions Magazine
August 2004

▶ Wireless Bluetooth® or 802.11b

Our wireless local area network (WLAN) solutions incorporate a user installable Cisco® PC card or factory installed Symbol Spectrum24® PC card (PCMCIA), which connects the 2t printer to a wireless network in ad hoc peer-to-peer or in infrastructure mode, and complies with the IEEE 802.11b interoperability standards for direct sequence wireless LANs. When the printer is configured with the integrated Bluetooth module, users can realize all of the convenience, power efficiencies and cost benefits of the WPAN.



▶ Magnetic Stripe Card Reader

The optional insertion magnetic stripe card reader provides route professionals the advantage of collecting payments and generating receipts while at the customer site. The insertion-style card reader provides outstanding reliability and is known for its ease-of-use.



Standard Features at a Glance

- Optional wireless local area network (WLAN) or wireless personal area network (WPAN) networking technologies.
- Supports a wide variety of hand-held computers from leading manufacturers.
- Exceptional print quality (203 dpi resolution).
- Fonts, graphics and operating system in Flash memory.
- Supports international character sets and any Bitstream® bitmap font.
- Increased label capacity using linerless label stock (optional).
- Supports the printing of graphics, 1D and 2D bar codes and signature capture.
- Intelligent power management and programmable sleep mode for extended battery life.
- Charging options include a low cost AC adapter or 12V vehicle cigarette lighter adapter.
- Optional Magnetic Stripe and Smart Card Reader.



2t

Specification Highlights microFlash® 2t Serial & Wireless Portable Thermal Printer

Physical Characteristics	microFlash® 2t	microFlash® 2t, Bluetooth®	microFlash® 2t, 802.11b
Dimensions	7.375" x 4.675" x 2.42" (18.8 x 11.9 x 6.2 cm)	7.375" x 4.675" x 2.42" (18.8 x 11.9 x 6.2 cm)	7.375" x 5.52" x 2.425" (18.8 x 11.9 x 6.2 cm)
Weight (printer only)	13.3 oz (0.337 kg)	15.1 oz (0.428 kg)	17.6 oz (0.499 kg)
Weight (with battery & paper roll)	23.3 oz (0.660 kg)	25.3 oz (0.717 kg)	27.6 oz (0.782 kg)
Drop Specification	6 ft (1.8 m)	6 ft (1.8 m)	6 ft (1.8 m)

User Environment	
Operating Temperature	-4° F to 131° F (-20° C to 55° C)
Storage Temperature	-40° F to 158° F (-40° C to 70° C)
Charging Temperature	41° F to 104° F (5° C to 40° C)
Relative Humidity	10% to 90% non-condensing
ESD Protection	8 kV Air, 4 kV contact

Communications	
Serial	RS-232, up to 38.4k baud (available on all models)
IrDA (2t only – not available in radio models)	IrDA compliant infrared data communications, up to 115.2k baud
Wireless LAN	Cisco® Aironet® 350 Series PC Card (PCMCIA) Symbol® Spectrum24® LA 4121 (PCMCIA)
Frequency Band	2.4 to 2.4897 GHz
Data Rates Supported	1, 2, 5.5 and 11 Mbps
Network Standard	IEEE 802.11b
Network Architecture Types	Infrastructure and ad hoc
Wireless Medium	Direct Sequence Spread Spectrum (DSSS)
Authentication	Open or Shared key
Encryption	None, 40 bit, 128 bit WEP
DHCP	Supported
DNS	Supported
Wireless PAN	Integrated Bluetooth module
Network Environment	Ad hoc or piconet network environments
Protocol	Supports version 1.1 and 1.2 of the Bluetooth standard (SIG certified)

Print Technology	
Printhead	Direct thermal, 384 dots across, 203 dpi (8 dots/mm)
Printhead Life	5,000,000 dot lines @ 25%
Print Speed	Up to 2" per second

Media	
Type	Direct thermal paper, labels, linerless labels (optional)
Capacity	2" maximum roll diameter
Width	2.25" (5.72 cm)

Power Source	
Battery	6V NiMH, 2150 mAh (DR10®)
DC Input 1	(AC Adapter) 12-15V, built-in spike and surge protection
DC Input 2	(Cigarette Lighter Adapter) 12-15V, built-in spike and surge protection

Battery Characteristics	
Type	6V NiMH, 2150 mAh (DR10)
Endurance	
Serial/IrDA	Prints approx. 9,690" or 1,615 – 6" receipts on a single battery charge
Bluetooth	Prints approx. 3,678" or 613 – 6" receipts on a single battery charge
802.11b	Prints approx. 1,980" or 330 – 6" receipts on a single battery charge
Spectrum24	Prints approx. 2,640" or 440 – 6" receipts on a single battery charge
Battery Life	80% of original capacity after 300 cycles
Recharging	2.5-3.5 hours from AC adapter or cigarette adapter

Fonts & Languages	
Memory Capacity	Flash/Ram Memory 2t, Serial/IrDA: 4/1 Mbit Flash/Ram Memory 2t Bluetooth, 802.11b: 8/4 Mbit
Standard Fonts	5.5CPI, 7.2CPI, 10.7CPI, 18.5CPI 20.4CPI & 22.6CPI (additional fonts available)
International Characters	Arab-T, Arab-S, Arab-E, Asian-A, Asian-B, shiftJIS, Greek, OCRA, OCRB, Unicode subset including Latin & Thai (additional international characters available)
Bar Codes	Prints 1D and 2D bar codes
Graphics	Supports storage of graphics/logos in Flash memory and transient "print once" graphics

Agency Approvals	
2t Serial/IrDA	FCC B, CE, C-Tick
2t Bluetooth, 802.11b	FCC B, CE, C-Tick, E-Mark

Warranty	
2 years (including printer case and printhead*)	

Options / Accessories	
• AC Adapter	• Depot Charger Kit
• Battery	• External Battery Charger
• Cigarette Lighter Adapter	• Magnetic Stripe/Smart Card Reader
• Cleaning Cards	• Paper/Labels
• Cleaning Kit	• Swivel Belt Loop
• Data Cables for Hand-Held Devices	• Swivel-Mount Bracket
• DB9 F Cable (coiled)	• Swivel-Mount Shoulder Strap
• DC Power Extension	

*When used with approved media grades.

Specifications are subject to change without notice. All product and company names are trademarks, service marks or registered trademarks of their respective owners.

Copyright 2006, O'Neil Product Development, Inc.
Part# 110174-001b 4/06 Made in the U.S.A.



email: info@oneilprinters.com

WWW.ONEILPRINTERS.COM

World Headquarters

O'Neil Product Development
8 Mason
Irvine, CA 92618-2705
Ph: 949.458.0500
Fx: 949.458.0708

AustralAsia

1/8 Railway Terrace
Dutton Park QLD 4102
Australia
Ph: +61 7 3255 3360
Fx: +61 7 3255 3365

EMEA

6 Joplin Court, Crownhill
Milton Keynes MK8 0JP
United Kingdom
Ph: +44 (0) 1908 635360
Fx: +44 (0) 1908 635361