

## KEY FEATURES

- VIA NANO™ 1.6 GHz w/ 1M L2 Cache
- Die-Cast Aluminum Alloy Housing for maximum heat diffusion
- Operates in a wide range of environments and temperatures. 14°F ~ 122°F (-10°C ~ 50°C)
- Available configurations w/ 2GB or 4GB DDR3
- Precisely designed, with strict revision control to maximize the system's lifecycle
- Stringent third party HALT / HASS tested for extensive temperature cycling, vibration, drop, shock, static electricity and emission tolerance



## KS6700 Series

### About Posiflex

Designer and manufacturer of Point-of-Service and industrial touch terminals

Revolutionary technology, reliable quality, reasonable pricing and recognized service

Delivers reliable terminals for maximum uptime and lower total cost of ownership

Comprehensive suite of peripherals and services

Over 25 years of innovative excellence with more than 30 patents for innovation

Global presence

Two ISO 9001/9002/14001 Certified Facilities

## The Enhanced Price Performer

The KS6715 now takes over where the KS6215 left off. Everything you loved about its predecessor, you will love even more in the KS6715 with its increased performance, ports, memory, and complete peripheral compatibility. It is a price-performer, giving you more for your hardware investment.

Featuring our patented aluminum chassis for maximum heat diffusion, a 1.6GHz CPU, it offers 110% more performance over its predecessor with its increased functionality. Providing even greater energy efficiency, look to the KS6715 for additional costs savings.

Available in a desktop configuration, which easily converts to a wall mount solution, it offers you adaptability and scalability to propel your business to greater heights.

Call today and find out how the KS6715 can boost your sales and help you grow your bottom line.

For more information call 888-968-1668 today!







**See the King Pin  
in POS Reliability!**

# Specifications

SPECIFICATIONS		KS6715	AVAILABLE SERVICES
Processor	VIA NANO™ 1.6 GHz w/ 1M L2 Cache		<ul style="list-style-type: none"> <li>• <b>Standard and Extended Warranty</b> Extend your depot warranty up to 5 years.</li> <li>• <b>Advance Exchange</b> We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.</li> <li>• <b>OnSite Service</b> Expert technicians will efficiently handle the complete equipment swap and return process.</li> <li>• <b>Regional Repair Depots</b> Three regional depots assure fast turn-around time on repairs.</li> <li>• <b>Post Warranty Support</b> Spare parts, in addition to a flat rate repair program, for post warranty needs.</li> <li>• <b>Installation Services</b> Let our nationwide network of experts stage and install your equipment.</li> <li>• <b>OEM Design and Integration</b> Our Product Development Team helps design equipment, for custom hardware applications.</li> </ul>
System Memory	DDR3 1066MHz SO-DIMM x1 Slot, (2GB Default)		
Memory Configurations	2GB or 4GB		
Power Supply	12V DC power adaptor, 60W		
Storage Device	2.5" SATA 160GB HDD or SSD Kit (Optional)		
Supported OS	POSREADY / POSREADY 7 / Win XP Pro / Win 7 Pro / Linux <sup>1</sup>		
DISPLAY			
LCD	15" TFT LCD, 1024x768 (XGA)		
Touch Function	5-Wire Resistive, USB Interface		
Brightness Control	Digital Push button		
Tilt Adjustment	From 15° to 70°		
PHYSICAL DIMENSIONS			
Dimensions (WxDxH)	Base Mount: 14.9" x 11.5" x 14.2"; Wall Mount: 14.9" x 2.71" x 12"		
Weight (Pounds)	Base Mount: 16 lbs; Wall Mount: 11 lbs		
CONNECTIVITY			
LAN Port	1 x RJ-45 10/100/1000 Base-T Ethernet		
Serial Port	4 x 9-pin male d-sub (5V/12V support on COM1/COM2/COM3/COM4)		
VGA Port	1 x 15-pin female d-sub RGB analog (12V support for Posiflex LCD Monitors)		
CR Port	1 x RJ-11 port controls 2 cash drawers		
Standard USB Port(s)	6 x USB 2.0 Type A port, (4 x on I/O panel, 2 x in side cover)		
Parallel Port	Optional (P/N: 21862033420)		



PERIPHERALS			
<b>Magnetic Stripe Reader - SD402</b> Biometric or Encrypted options 	<b>Rear Mount Display - PD2604</b> 2 x 20 Character VFD* 	<b>Thermal Printer - PP8000</b> 80mm Wide, Printing Speed: 220mm/second 	<b>Cash Drawer - CR6300</b> Printer Driven and USB options available 

\*Vacuum Fluorescent Display  
<sup>1</sup>Driver Support Only

See [www.PosiflexUSA.com](http://www.PosiflexUSA.com) for a complete line of peripherals

**POSIFLEX™**  
 Be the Pioneer, Be the Leader  
 30689 Huntwood Avenue  
 Hayward, CA 94544  
 Toll-free: 888.968.1668  
 Phone: 510.429.7097  
 Fax: 510.475.0982  
 E-mail: [sales@posiflexusa.com](mailto:sales@posiflexusa.com)  
[www.posiflexusa.com](http://www.posiflexusa.com)

