



Improved working efficiency and service quality with high availability
Fan-Free POS terminal KS-6800 series



Posiflex presents the brand new Fan-free touch terminal KS-6800 Series with Intel solution, 12"/15" touch screen and a small footprint in order to meet this demand. The KS-6800 Series applies Intel ATOM N270 1.6G CPU, SATA HDD, 1 Gigabyte Ethernet as well as the connect ports of USB, Serial, VGA and CR ports. In addition, it also supports the optional peripherals items such as MSR and CF memory card reader.

Optional RAID 1 function for KS-6815 provides an advanced feature for user, which could satisfy the data protection. It is also supports SteelVine Manager management software, error POP UP notification and SMTP e-mail notification. This product is suitable for the Public Sector, Retail, Hospitality and Kiosk market segments.

- High performance ATOM 1.6G CPU and support 2 x SATA 2.5" HDD
- Fan free structure for harsh environment
- Dust & Water Resistance up to IP44 (KS-6815, Option)
- DDR2 SODIMM memory can extend to 2 GB
- Support Win XP Pro, POSReady, WEPOS and Linux environment
- High quality 12" or 15" TFT active matrix LCD panel with 1024 x 768 resolution
- Vertical type LCD panel with easy tilt angle adjustment
- VGA memory size program by software up to 128 MB
- Durable resistive type touch sensor for broad range of application
- Supports power saving by suspension mode
- Supports SSD (Solid-State Drive) Data Storage Device
- Data storage device: 2.5" SATA HDD or optional CF card reader
- An advanced slim base designed supports storage room with 2nd 2.5" SATA HDD for optional RAID 1 Function for KS-6815
- Optional RAID Function For KS-6815 with supports of:
 - ◉ RAID 1(Disk Mirroring)
 - ◉ 2 x SATA I or SATA II HDD
 - ◉ Management software via SteelVine Manager
 - ◉ POP UP error notification
 - ◉ Support POSReady, WEPOS, XP pro and Linux
 - ◉ SMTP e-mail notification



Fan-free



CPU



Touch Sensor



12"/15" LCD

Posiflex Fan-Free POS Terminal



| Specification | KS-6812 | KS-6815 |
|-------------------------|---|---|
| CPU | Intel Atom CPU, N270 1.6G | |
| VGA Interface | D-SUB | |
| VGA Memory | Share system memory up to 128MB | |
| LCD Display | 12" 1024 X 768 | 15" 1024 X 768 |
| DRAM Memory | DDR-2 400/533MHz, SO-DIMMx2, Max 2G | |
| Serial Port | 3 X, DB9 X 2, RJ-45 X 1 (RJ-45 to DB9 Cable Optional) | |
| Parallel Port | N/A | Yes, proprietary port connector (conversion cable optional) |
| CF Card Slot | Option | |
| CR Port | Yes, one connector control 2 Cash Drawer | |
| Standard USB Port | 6X,(4X ports on the I/O plate, 2X port on left side) | |
| Audio Port | Line-Out | N/A |
| Ethernet Port | 10 / 100 / 1000 Mb | |
| UPS Port | N/A | Yes |
| Touch Controller | USB interface | |
| Touch Sensor | 5 wires | |
| Wireless LAN | Option | |
| Storage Device | 2.5" SATA HDD or SSD HDD | |
| Power ON Wake Up | Through Alarm / LAN / Modem | |
| Mechanical Installation | Desk Top or Wall mount | |
| Power Saving | Suspension mode | |
| Indicator LED | Bi-color LED indicators | |
| Brightness Control | By push switch | |
| Dimensions (WxDxH) | 309.9 X 262.3 X 288mm (12.2"X10.3"X11.3") | 378 X 304 X 364mm (12.5"X12.0"X14.3") |
| Weight (N. W. in kg) | 4.1 kg | 7.7 kg |
| Fanfree system | Yes | |
| Speaker Build In | 2W speaker in main unit | |
| OS Support | POSReady, WEPOS, XP pro, Linux | |
| Option peripheral | | |
| RAID Function | N/A | RAID 1 (Disk Mirroring) |
| MSR | SD-680: 2/3 tracks modular on Right Side of LCD panel | SD-400/SD-400Z: MSR and/or Finger print sensor |
| Wireless LAN | 802.11 b/g with USB interface | |
| CF Card Slot | Type II, memory card only | |
| Customer Pole Display | PD-2605: VFD pole display PD-309: LCD pole display | PD-2604: VFD pole display PD-2602: VFD pole display PD-2501: VFD pole display PD-310: LCD pole display PD-306: LCD pole display |
| 2nd LCD Display | N/A | 12" LM-6101B; 15" LM-6501B, VGA Port |
| 2nd HDD | N/A | Yes |
| SSD Storage Device | Support SATA I (150MB/s, 8G) | |
| UPS Battery | N/A | 2.3 Ahr / 12V |

** The product information and specifications are subject to change without prior notice.



Posiflex Technology, Inc.
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

