

# POS X

POINT OF SALE  
PERFECTED

## XTS4000 SERIES

LCD TOUCH MONITOR

The XTS4000 Series LCD touchscreen monitor has been designed to outperform its competition in both quality and value. With pin-point accuracy, the crisp image and intuitive controls make this a must-have component in any next-generation point-of-sale system. The splash-resistant screen, extra-thick LCD glass and solid bump free operation make the XTS4000 a great choice for Restaurants, Cafes, Autosshops or any location in need of touch functionality.



### KEY FEATURES

- Dual video inputs come standard (VGA and DVI-I)
- Optional integrated MSR and Customer Display
- 15" and 17" active matrix displays available
- USB Touch interface maximizes compatibility
- Bump-free 90-degree tilting base
- VESA mountable
- 3 year warranty

LCD TOUCH MONITOR

# XTS4000 Series Specifications

PART NUMBER	XTS4000	XTS4170
<b>PANEL SIZE</b>	15" TFT Active Matrix Display	17" TFT Active Matrix Display
Display Area	11.97" (W) x 8.98" (H)	13.3" (W) x 10.6 (H)
Touch Screen	5-Wire Resistive, 2.8mm glass, 35+ millions taps per location	
Resolution	SVGA 800 X 600 XGA 1024 X 768	SVGA 800 X 600 XGA 1024 X 768 SXGA 1280 X1024
Touch Active Area	11.95" 8.96"	13.25" x 10.75"
<b>DISPLAY</b>		
PC Video Interface	Analog RGB (VGA) & 24 pin DVI-I	
Brightness	250 cd/m2	
Pixel Pitch	0.011" X 0.011"	
Colors	16.7 million colors	
Contrast Ratio	300-500 :1	450 : 1
On Screen Control	Auto Configure, Brightness, Contrast, Phase, H-position, V-position, recall	
Back Controls	Power on/off with LED, menu, auto tune, adjustment(+/-)	
Viewing Angle	160°	
Housing	ABS Housing	
<b>PHYSICAL</b>		
Dimensions	14.9"(w) x 12.25"(H) x 9.25"(D)	16.5"(w) x 14"(H) x 9.25"(D)
Weight	13.5 lbs	15.5 lbs
Tilt Angle	0° to 90°	
Housing Color	Black	
Stand Style	Cable Management Base	
Mounting Options	Desktop Placement, VESA 75mm x 75mm	
<b>ELECTRICAL</b>		
Adapter Input	100-240 VAC, 50-60Hz	
Adapter Output	12 VDC, 3A (C+)	
<b>ENVIROMENTAL</b>		
Temperature Operating	32° F to 114° F operating	
Temperature Storage	-4° F to 140° F	
Humidity	10% - 90% non-condensing	
<b>WARRANTY</b>	3 Year Limited	
<b>CERTIFICATIONS</b>	FCC, CE, MIC, UL, RoHs	
<b>OPERATING SYSTEM</b>	DOS/WIN NT 4/WIN 9X/WIN ME/WIN 2000/WIN CE/XP/VISTA/Linux/Mac	

<b>ACCESSORIES</b>	
XM130U	3 Track MSR with USB interface
XM130K	3 Track MSR with KBW interface
XP2200S	Integrated Customer Display

