

StealthTouch

M2

All-in-one



M2 S-Line

Built-in Printer



efficient performers

The StealthTouch - M2 is a state-of-the-art 12" all-in-one powered by Intel's Atom processor. The low - power Atom processor allows the M2 to save electrical energy without sacrificing performance. The M2 further boosts energy efficiency by utilizing an LED LCD, which consumes less power than a traditional TFT LCD.

The S-Line model redefines the all-in-one design by integrating a 3" thermal receipt printer with the touchcomputer. The S-line can load the most commonly used paper size, 80mm (3 1/8") wide by 80mm (3 1/8") diameter. The most exciting feature of the S-line is the printer's tool-less "slider" design. It allows the printer to be easily replaced in the field in less than a couple minutes, without affecting the main terminal.

With its compact footprint, the M2 Series takes up little countertop. And with its variety of integrated peripherals, the M2 can free up your premium counter space that can be used to display impulse merchandise and advertisements that will generate additional revenues.

Specifications

Model	M2	M2 S-line
Display Size	12" LED LCD	12" LED LCD
Printer Built-in (field replaceable)	No	3" Thermal, 23 lines/sec Driver: Epson ESC, OPOS Interface: Serial or USB Paper: 80 mm (3 1/8")
Dimensions (WxHxD)	12.2" x 11.7" x 10.0"	12.2" x 13.7" x 12.75"
Wallmount (WxHxD)	12.2" x 10.2" x 3.0"	No
Weight (Wallmount)	14 lbs (8 lbs)	21 lbs
Touchscreen	Resistive 5-wire	
Spill Resistance	Yes (front panel)	
Processor	Intel Atom DualCore 2GHz, Dual Core 1.9GHz, Core 2 Duo 2.5GHz	
Memory	2GB, up to 4GB	
Video	Intel GMA950, 128MB	
Storage	Hard Drive, or Solid-state Disk	
Operating System	Windows 7 Prof, POS Ready, Windows 7 Embedded, Linux	
Network/Ethernet	Intel Gigabit	
WiFi	Optional (Intel RF 802.11 a/g/n)	
USB 2.0	6	
Powered USB	1 x 12V, 1 x 24V	
Serial Port	4	
Parallel Port	Optional	
Cash Drawer Port	1 (Epson emulation, 24V)	
External (2nd) VGA	1	
Speakers	Optional (2 x 2 Watts)	
Security Lock	Bolted (4 mm screw), or Kensington MicroSaver	
Operating Environment	0° C to 40° C, 20% to 80% Humidity	
Power Supply	120W, AC 100-240V	
Color	Black	
Agencies	FCC A, CE, UL	
Integrated Peripherals	Magnetic Stripe Reader Biometric Reader (Digital Persona U.R.U) Rear Customer Display or LCD Proximity RFID Reader Webcam Privacy Filter	



**MSR +
Biometric**



Dual Display



**S-Line
(built-in printer)**



<http://www.pioneerpos.com>
info@pioneerpos.com
 Tel: 888-468-9757



All trademarks belong to their respective companies.
 Specifications subject to change without notice.