

## Stealth-M1: Specification

For more assistance, please contact <support@pioneerpos.com>, or 909-468-9757.

<b>Display</b>	10.1" LCD, LED backlight, 1366x768 resolutions
<b>Touchscreen</b>	Resistive (5-wire)
<b>Chipset</b>	Intel NM10 Express Chipset
<b>Processor</b>	Intel Atom D2550 1.86GHz
<b>Memory</b>	2GB, up to 4GB DDR3
<b>Video</b>	Intel GMA HD3650, 1024MB
<b>Storage</b>	Hard Drive, Solid-state Disk, or Secure Digital
<b>Operating System</b>	Windows 7 Professional, Windows Embedded Standard 7, POSReady 7, Linux
<b>Network/Ethernet</b>	Intel 10/100/1000 BaseT
<b>WiFi (wireless)</b>	RF 802.11 a/g/n (optional)
<b>Serial Port</b>	2
<b>USB 2.0</b>	3
<b>Power Out, +24 volts</b>	1
<b>Secure Digital Reader</b>	1 (supports up to 64GB)
<b>Speakers</b>	Optional (2 x 1 Watt, Stereo)
<b>Security Lock</b>	Bolted (6mm screw) or Kensington MicroSaver
<b>Bezel Color</b>	Grey
<b>Operating Temperature</b>	0° C to 40° C
<b>Operating Humidity</b>	20% to 80%
<b>Power Supply</b>	External, 150W, AC 100-240V
<b>Agency Approvals</b>	FCC-A, CE
<b>Mounting Options</b>	Standard: Printer Base (Epson TM-T70 built-in) Option: Wall or VESA mount
<b>Integrated Add-ons</b>	Magnetic Stripe or Barcode Slot Fingerprint/Biometric Reader (DigitalPersona) Rear Customer Display or 10" LCD Barcode Scanner (Omni-directional) Proximity RFID Reader