

MS100 Wand Scanner

Optical

Light Source **Receiving Device** Depth of Field Resolution Print Contrast Scan Rate **Reading Angle** Ambient Light

650 ~ 660nm Red LED Photo Sensor 0.04" (1.0mm) 5 mils (0.127mm) 0.6 minimum 4 ~ 24 inches/second (10 ~ 60 cm/second) 45° to 90° 5000 Lux/Max

Functionality

Symbologies Codabar, Code 11, Code 32, Code 39 (standard and full ASCII) Code 93, Code 128, EAN-8, EAN-13, Label Code IV and V, MSI Code, Plessey Code, Standard 2 of 5, UPC-A, and UPC-E

Interface USB, Keyboard wedge, RS232, or TTL (undecoded)

Length 5.5" (140mm)

Mechanical and Electrical

Dimensions:

Cable

Diameter 1.2" x .9" (30mm x 23mm) Weight: 76a 71" (180 cm) Case Material **ABS** plastic 5V DC ±10% Supply Voltage Surge Power <800mA Working Current 60mA ±10mA

Environmental:

32°F to 122°F (0°C to 50°C)
-4°F to 140°F (-20°C to 60°C)
20% to 85% RH non-condensing
5' (1.5m) drop to concrete



Los Angeles Miami Mexico http://www.ute.com http://latin.unitech-adc.com e-mail: inquiry@ute.com e-mail: info@latin.uniteeh-adc.com

Unitech APAC

Taipei http://www.unitech-adc.com e-mail:aidcsales@adc.unitech.com.tw

Unitech Japan

Tokyo http://www.unitech-japan.co.jp e-mail: sales@unitech-japan.co.jp

Unitech Europe

Tilburg / NL Wiltshire / UK http://www.unitech-europe.nl http://www.unitech.co.uk e-mail: sales@unitech-europe.nl

Unitech Greater China

Beijeng Suzhou Shanghai Guang Zhou Xiamen Taipei http://www.ute.com.cn unitech@ute.com.cn http://adc-utt.unitech.com.tw barcode@unitech.com.tw

Head Office

http://www.unitech.-adc.com e-mail: marketing@adc.unitech.com.tw

Specifications subject to change without notice. Copyright 2005 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All products and company names are trademarks, service marks or registered trademarks of their respective owner

MS100 Wand Scanner

Features

• Rugged, lightweight design

• Easy to use and configure

• Low power consumption

• Advanced Data Editing

• User configurable via PC programming

• Wide read angle

High scan speed

The MS100 bar code wand is targeted toward low reading volume / cost

effective solutions. The advanced optics and electronic design converts bar code labels into a high quality digital signal. Able to read color, faded, and

low contrast barcodes quickly and accurately, the MS100 is a proven solution.

Its shape gives the MS100 the comfort and handling of a conventional ink

pen. Just sweep the tip of the wand across the bar code in either direction and listen for the "good read" beep that lets you know the data has been

• Available with TTL, keyboard wedge, RS232, and USB interfaces

successfully captured. It doesn't get easier than that.

Unitech America