

# PA600

# Mobile Clinical Assistant



#### PA600 Mobile Clinical Assistant – RFID Reader for Multiple ISO Standards

The Unitech PA600 Mobile Clinical Assistant (MCA) is a compact and rugged mobile computer with an integrated 13.56MHz High Frequency RFID reader. The PA600 MCA innovatively supports ISO15693, ISO14443A and ISO14443B standards in a single device, making it ideal for a range of RFID applications.

#### Supports a Range of Applications

Traditionally RFID devices would only support one ISO standard, requiring a different device for each application, but now, this one device does it all, supporting multiple applications in the same organization and across a range of markets.

Enhance patient security by reading RFID cards to verify nurse and patient identity and record the administration of drugs. The PA600 MCA can also perform ticket inspection for transportation applications. Or used by museum visitors to read tags containing information about exhibits.

There is a growing demand in today's healthcare environment to implement RFID technology for improved point-of-care accuracy, efficiency and overall patient safety. For example, patients in the hospital would have an identification bracelet with an RFID tag and 2D bar code to ensure all medical procedures, such as blood draw and medication distribution, are treated to the correct person. The Unitech PA600 MCA is specifically designed for these applications with its antimicrobial enclosure and integrated RFID/2D bar code readers.

#### Seamless RFID Integration

Supporting Oracle Database Lite and Microsoft BizTalk Server 2006, the PA600 MCA allows end users to synchronize RFID data with existing business systems and databases. Support for Wavelink Avalanche enables easier management of wireless devices, decreasing cost and time of deployment.

### Lightweight, Ergonomic Design

The PA600 MCA weighs just 11 ounces and is small enough to fit into your shirt pocket. But don't let its size fool you - with a 520MHz processor and an IP64 rating, the PA600 MCA is a powerful industrial device.

The PA600 MCA features an ergonomic design to ensure easy operation and user comfort. A full QVGA touchscreen enables the operator to view more information about the RFID tags that have been read and a compact alphanumeric keypad makes data entry simple.

## Tough Enough for All Environments

The rugged design of the PA600 MCA ensures performance under harsh environments. Thanks to its IP64 rating, the PA600 MCA is resistant to dust and moisture. Its robust build is able to withstand multiple 4ft drops to concrete without risk of damage. Thus minimizing device downtime, reducing repair costs and delivering a much lower total cost of ownership.

#### Main Features

- Supports three ISO standards in one device: ISO15693, ISO14443A, ISO14443B
- · Windows Mobile 6.1
- Integrated HF RFID reader, keypad and touch screen, or 2D bar code scanner
- Built-in Bluetooth and WLAN
- IP64 rated
- SDIO expansion slot
- Full range of accessories and chargers
- Supports Oracle Database Lite, Microsoft BizTalk Server 2006 and Wavelink Avalanche













System

CPU 520MHz Intel PXA270 Processor Memory Flash: 512MB, SDRAM: 128MB

OS Windows Mobile 6.1

Display

240 x 320 QVGA, Color Transflective TFT, with Touch Screen & backlight

Keypad

18-key, including numeric key, alpha key and function key

Input Device

HF RFID Reader, Keypad, Touch Screen, and Full Alphanumeric Software Keyboard, 2D Bar Code Scanner

RFID Reader

Frequency: 13.56MHz

Tag Support: ISO15693, ISO14443A, ISO14443B

Indicator

LED

Communication

USB Host & Client 802.11b/g

Bluetooth (Supports Printer, Modem, and ActiveSync)

Audio

MIC

Speaker

**Headset Connector** 

Receiver

Expansion Slot

SDIO Slot









Unitech America

Los Angeles, Houston, Guadalajara http://www.ute.com e-mail: inquiry@ute.com http://latin.unitech-adc.com e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei

http://www.unitech-utp.com.tw e-mail: aidcsales@tw.ute.com

**Unitech Japan** 

Tokyo

http://www.unitech-japan.co.jp e-mail: sales@jp.ute.com

Power Source

Main Battery 3.7V 2200mAH Li-ion battery
Backup Battery Rechargeable Ni-MH backup battery

Environmental

Operating temperature 14°F to 122°C Storage temperature -4°F to 140°F

Relative Humidity 5% ~ 95%(non-condensing)

Drop test to Concrete 4 feet Environmental Sealing IP64

Antimicrobial housing

Weight 11oz with battery
Dimensions 5.9"L x 3.3"W x 1.4"H

Recommended Cleaning Solutions

Sani-Cloth® HB Sani-Cloth® Plus Super Sani-Cloth® CaviWipes™ Virex® 256

409® Glass and Surface Cleaner

Windex® Blue

Gentle dish soap and water

Note: The PA600 MCA's antimicrobial housing can be disinfected with cleaning agents made of less than 75% alcohol. The use of bleach will weaken the strength of the unit and is not recommended.

Software

Unitech Software Development Kit

Oracle Database Lite Wavelink Avalanche

Microsoft BizTalk Server 2006 R2

Accessories

4-Slot Multi-Bay Cradle Battery Charger
Desktop Cradle Extended Battery

Holster Vehicle Quick Charging Cable

Vehicle Dock

Regulatory Approvals

CE, FCC, BSMI, VCCI, CCC, RoHS compliant

Unitech Europe

Tilburg / Netherlands

http://www.unitech-europe.com e-mail: sales@eu.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://www.ute.com.cn unitech@cn.ute.com

Taipei http://adc-utt.unitech.com.tw barcode@tw.ute.com

**Head Office** 

Taipei

http://www.unitech-adc.com e-mail: marketing@tw.ute.com

RFID team e-mail: rfid@tw.ute.com