

P310F



## P SERIES CARD PRINTERS



### Fast, Monochrome, High-Quality Plastic Card Printing Has Never Been Easier

The Eltron P310F is ideal for printing single-sided monochrome cards, adding hologram overlays, or scratch-off panels to preprinted cards. The P310F is the most affordable card printer in its class.

Use the P310F to add personalization in black, or other monochrome color, on preprinted cards. It can also be used to apply a hologram overlay to preprinted cards to provide additional security. The P310F has the ability to print on any area of a card permitting endless flexibility in card design.

Use the P310F for:

- Printing plastic cards in monochrome
- Adding personalization to preprinted cards
- Creating durable business cards, employee/visitor badges
- Adding a holographic overlay to preprinted cards

The P310F utilizes a proven, reliable print engine for fast accurate printing. It produces sharp, readable bar codes, line art, graphics and text in seconds. Featuring a small footprint, the P310F is perfect for desktop applications.

The P310F is operator-friendly, easy-to-load, and features a low maintenance design making it simple for anyone to use. Green, yellow and red LED indicators provide easy to understand printer status. An easy to change, self-cleaning cartridge thoroughly removes dust on cards before printing, minimizing problems caused by contamination.

You can rely on Eltron Card Printers for high quality and dependability because they are manufactured to exacting standards and are ISO 9001 certified.

# P310F Specifications

## General Specifications

- High speed printing, 1000 cards/hour, edge to edge, monochrome
- 2 MB image memory standard
- Small footprint
- Easy to use WindCard Classic™ utility tool standard
- Windows® Drivers for 95/98 and NT 4.0
- One year printer warranty
- One year (unlimited passes) printhead warranty<sup>1</sup>
- Powerful EPCL (Eltron Printer Command Language)

## Monochrome Printing

- Monochrome thermal transfer printing
- 1000 cards/hour (3.5 seconds per card), edge to edge
- 300 dpi (11.8 dots/mm) print resolution
- Edge to edge printing standard

## Bar Codes

- Code 39
- Code 128 B & C with & without check digit
- 2 of 5 & 2 of 5 Industrial
- UPC-A
- EAN 8 & EAN 13
- PDF-417 2D bar code and other symbologies available via Windows driver and WindCard Classic utility tool

## Fonts

- Resident: Arial Normal 100, Arial Bold 100
- True Type fonts available via Windows driver and WindCard Classic utility tool

## Card Specifications<sup>1</sup>

- Types: PVC, Composite PVC
- Card width/length: ISO CR-80 - ISO 7810, 2.125" (54mm) X 3.385" (86mm)
- Option: Magnetic Stripe - ISO 7811
- Option: Smart Card - ISO 7816-2
- Card thickness: 10 mil (.25mm) to 60 mil (1.524mm)
- Card Cartridge capacity: up to 210 cards (10 mil), up to 75 cards (30 mil)
- Card Output Hopper capacity: up to 210 cards (10 mil), up to 75 cards (30mil)

Note 1: For optimum performance use Zebra/Eltron media

Note 2: Dimensions without Card Cartridge and Card Output Hopper

## Ribbon Specifications<sup>1</sup>

- Monochrome: 1500 cards/roll
- Monochrome colors: black, red, blue, green, yellow, silver, gold, white, Scratch-Off Gray
- K Resin + O: 800 cards/roll

## Overlay Varnish Specifications<sup>1</sup>

- Thermal transfer
- Clear and holographic options available:
  - Clear
  - Genuine/Secure hologram
  - Pcard hologram
  - Custom hologram

## Communications Interface

- Parallel standard (parallel cable included)
- RS232C serial optional

## Mechanical<sup>2</sup>

- Width: 12.4" (315mm)
- Depth: 7.75" (198mm)
- Height: 8.7" (220mm)
- Weight: 13.4 lbs (6.1kg)

## Electrical

- 110 ~ 230 Volts AC, 60 ~ 50 Hz
- FCC Class A, CE, UL and CUL approved

## Environmental

- Operating Temperature: 60°F to 86°F (15°C to 30°C)
- Operating humidity: 20% to 65% non condensing
- Storage temperature: -23°F to 158°F (-5°C to 70°C)
- Storage Humidity: 20% to 70% non-condensing
- Ventilation: Free air

## Options

- RS232C serial port (EPCL recommended for fast throughput)
- Smart card contact station (30 mil cards only)
- Magnetic encoder (30 mil card only)
- Extended warranty program
- Hot swap warranty program
- Cleaning supplies



Club Membership



Employee Badge



Business Card



Membership card



©1999 Zebra Technologies Corporation. All Rights Reserved. Specifications subject to change without notice. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. 820007-046A

## American Operations

**Zebra Technologies Corporation**  
1001 Flynn Road  
Camarillo, CA 93012-8706  
United States of America  
Telephone: +1 805 579 1800  
Fax: +1 805 579 1808  
Toll free in US: 800 452 4056  
e-mail: cards@eltron.com  
Web: www.eltron.com

## European Headquarters

**Zebra Technologies Corporation**  
Zebra House  
The Valley Centre, Gordon Road  
High Wycombe  
Buckinghamshire HP13 6EQ, UK  
Telephone: +44 (0) 1494 472872  
Fax: +44 (0) 1494 450103  
e-mail: eurosales@eltron.com

## Asia Pacific Headquarters

**Zebra Technologies Corporation**  
1 Sims Lane #06-11  
387355 Singapore  
Telephone: +65 8420 322  
Fax: +65 8420 514  
e-mail: asiasales@eltron.com