



# P420i

## PERFORMANCE



### Dual-Sided Color Card Printing is Easier and Faster Than Ever

The Zebra P420i card printer is a robust, dual-sided card printer with an LCD display and convenient easy-to-use features for producing high quality, personalized photo ID cards on-demand for high volume applications.

Use the P420i to print:

- » Employee/Student ID cards
- » Time and Attendance cards
- » Access Control cards

### Zebra P420i Advantages

**Advanced Color Printing:** Enhanced color-processing firmware and new richer color formulation

**Reliable Operation:** Full metal enclosure and field-proven reliable P310 print engine. Reject hopper separates cards that fail encoding prior to printing

**i Series Intelligent Printing System:** Enhanced i Series functionality makes high image quality card printing a simple function for all users. The system features:

- » Advanced RFID Technology
- » Automatic Driver Configuration
- » Intelligent Color Optimisation
- » Ribbon Image Counter & Ribbon Low Notification
- » Enhanced Ribbon Formulation

### Basic Specifications:

- » 35 Seconds/Card Print Speed (YMCKOK)
- » Two-line LCD display with printer status and user commands
- » Full metal enclosure with viewing window
- » Full Color or Monochrome Dual-Sided Card Printing
- » Parallel or USB Interface
- » 100 Card Capacity Feeder
- » i Series Printers require the use of TrueColors™ i Series ribbons for full color printing

# P420 Card Printer

## iSeries



**Card  
Printer  
Solutions**

# P420i

## Card Printer Product Specifications



### General Specifications

- » High speed printing
- » 102 cards/hour full color, single-sided (YMCKOK)
- » 4MB image memory standard
- » Standard card flip over feature for dual-sided printing
- » Windows® drivers for 98, NT, 2000, ME, XP
- » Bi-directional driver communication
- » One year printer warranty
- » One year (unlimited passes) printhead warranty
- » Pass-code electronic lock

### Color Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 35 seconds per card full color single-sided (YMCKO/K)
- » 300 dpi (11.8 dots/mm) print resolution

### Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

### Fonts

- » True Type fonts via Windows driver

### Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811 » Smart Card-ISO 7816-2
- » Card thickness: 30 mil (.76mm) to 60 mil (1.524mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 100 cards (30 mil)

### Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

### Ribbon Specifications

- » i Series Printers require the use of i Series ribbons for full color printing
- » Monochrome: 1500 & 1000 cards/roll
- » Monochrome colors: black, red, blue, green, silver, gold white & scratch-off grey.
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » YMCKOK: 170 cards/roll
- » YMCKO: 200 & 330 cards/roll
- » Overlay varnishes: thermal transfer, clear and holographic overlays available



### Communications Interface

- » Centronics Parallel (parallel cable included)
- » USB Option
- » Ethernet Option

### Mechanical

- » Width: 20.90in (523mm)
- » Depth: 10.17in (253mm)
- » Height: 10.76in (269mm)
- » Weight: 27.5lbs (12.5kg)

### Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

### Options

- » USB Interface
- » Ethernet
- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only)
- » Cleaning supplies
- » Service manual

<http://cards.zebra.com>

\* Optimised for use with Zebra Media



Zebra Technologies Corporation



An ISO 9001 registered company ©2003 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. P420-10/03

#### North America

Zebra Technologies Corporation  
Card Imaging Division  
1001 Flynn Road  
Camarillo, CA 93012-8706  
USA  
Telephone: +1 805 579 1800  
Fax: +1 805 579 1808  
Toll free in US: 800 452 4056  
e-mail: cards@zebra.com

#### Europe, Middle East, Africa

Zebra Technologies Corporation  
Card Imaging Division  
The Valley Centre, Gordon Road  
High Wycombe  
Buckinghamshire HP13 6EQ, UK  
Telephone: +44 870 241 1527  
Fax: +44 870 241 0765  
e-mail: eurosales@zebra.com

#### Asia Pacific

Zebra Technologies Corporation  
Card Imaging Division  
1 Sims Lane #06-11  
387355 Singapore  
Telephone: +65 6858 0722  
Fax: +65 6885 0836  
e-mail: asiasales@zebra.com

#### Latin America

Zebra Technologies Corporation  
Card Imaging Division  
6175 NW 153rd St. #121  
Miami Lakes, FL 33014  
USA  
Telephone: +1 305 558 3100  
Fax: +1 305 558 8485  
e-mail: latinsales@zebra.com